

FP-22

High Temperature Furnace Condensate Removal Pump

The FP-22 is a true furnace condensate pump designed specifically to handle harsh condensing furnace applications. The FP-22 will accommodate high temperature and acidic condensate that is typical in these type of applications.

With a 1/2 gallon tank, this pump is constructed from glass filled nylon resin and steam resistant electronics that can handle water temperatures up to 190°F. This pump also incorporates additional design features including built-in P-Traps, high level alarm switch and a reversible contoured top deck to reduce condensate spillage. A check valve prevents condensate from flowing back into the pump and odors from drain pipes.



Features:

- *Built-in P-Traps saves installation time*
- *Steam Resistant Electronics prevents damage in harsh conditions*
- *Hot Water Safe up to 190°F*
- *Contoured Decking reroutes moisture accumulation back into tank*
- *Reversible Deck for maximum installation flexibility*
- *Thermal Overload Protection*
- *Stainless Steel Pump Shaft*
- *LED indicators lights conveniently shows pump status*
- *90 degree turn check valve for easy servicing*

| Model | FP-22 | FP-22-230 |
|---------------------|--------------|-------------|
| Max Flow | 122 Gal/Hr. | 144 Gal/Hr. |
| Max Head | 22' | |
| Tank Capacity | 1/2 Gallon | |
| Power | 120V / 1.9A | 230V / 1.0A |
| Hz | 60 Hz | |
| Discharge Line Size | 3/8" | |
| High Level Alarm | Dry Contacts | |
| Height | 6.25" | |
| Inlet Height | 4.25" | |
| Length | 11.5" | |
| Width | 5.5" | |
| Cable Length | 6.0' | |

| Catalog No. | Description | UPC | UOM | Order Multiple | List Price |
|-------------|---|-------------|-----|----------------|------------|
| FP-22 | FP-22 Condensate Pump, 22ft. lift, 120V | 95247156481 | Ea | 6 | \$196 |
| FP-22-230 | FP-22 Condensate Pump, 22ft. lift, 230V | 95247156498 | Ea | 6 | \$196 |