

Fireeye Nexus™ Bracket and Coupling Accessories

DESCRIPTION


Fireeye's extensive line of mounting hardware and shaft couplings make applying both the Nexus NX and PPC series of parallel positioning controllers nearly fool proof. Fireeye's unique "D" hole coupling design virtually eliminates the possibility of the servomotor and shaft slipping. Fireeye couplings do not rely on setscrews on the shaft to maintain proper connection, because the flatted or "D" hole design is a perfect fit to Fireeye servo motor shafts. The shaft end also has a "D" hole and when used with the available filing guide, make a perfect fit here as well.

All Fireeye mounting brackets are made of heavy gauge steel and powder coated for a durable finish. All motor mounting holes are kept to close tolerances to lessen the amount of movement should the motor mounting bolts become loosened.

Where direct coupling of the motor to the valve or air damper is impractical, Fireeye offers several Industrial Crank Arms.

Cleaver Brooks

Fireeye offers a complete series of kits to make retrofit of Cleaver Brooks boilers easy. Each kit is designed to reuse the Cleaver Brooks oil metering valve or gas butterfly valve. This assures the installer an incorrectly designed or sized replacement valve will not compromise the firing rate. The gas/oil kit comes complete with a replacement oil cam and shaft coupling that replaces the OEM cam eliminating the intermediate adjusting screws and spring. The gas valve bracket fits the bolt pattern after removal of the over travel hardware. Air register drive arm and bracket. Optional FGR kit is also available for the "LE" style boiler.




Couplings



Fireye offers an extensive line of servomotor shaft couplings. Each coupling has flattened “D” holes on both the motor and driven shaft end. Available in a wide range of sizes these couplings, when used with the available shaft filing guide, assure a direct connection that will not rotate even if the setscrews loosen. For FGR damper applications, where thermal expansion of the damper shaft may cause thrust loading of the motor shaft, Fireye offers a unique expandable flexible coupling.


Industrial Crank Arms

For applications that do not lend themselves to a direct connection between the servomotor and the shaft Fireye’s industrial crank arms can be used. These arms consist of a splined “D” hole mounting hub and arm. The hub provides for thirteen separate mounting positions allowing the arm to be oriented properly. Tightening a small setscrew in the arm eliminates any slight play between the hub and arm. This setscrew is located so as to fit between spline teeth in the hub. The arm is secured to the hub by a lock nut. Each arm has three pivot holes; 3, 4 and 5 inches and 6, 7 and 8 inches



Custom Brackets and Couplings

Fireye has provided custom brackets for a variety of applications. We can fabricate to your specifications.





Fireye Part No.	Description
NXCBO3FT	Cleaver Brooks Firetube, Gas Only, 3 inch Gas Valve
NXCBOFT	Cleaver Brooks Firetube, Oil Only
NXCBO3OFT	Cleaver Brooks Firetube, Gas/Oil, 3 in. Gas Valve
NXCBO4FT	Cleaver Brooks Firetube, Gas Only, 4 in. Gas Valve
NXCBO4OFT	Cleaver Brooks Firetube, Gas/Oil, 4 in. Gas Valve
NXCBOFGR	Cleaver Brooks Firetube FGR Bracket with Coupling
NXCBO3WFT	Cleaver Brooks Watertube, Gas Only, 3 in. Gas Valve
NXCBOFT	Cleaver Brooks Watertube, Oil Only
NXCBO3WFT	Cleaver Brooks Watertube, Gas/Oil, 3 in. Gas Valve
NXCBO4WFT	Cleaver Brooks Watertube, Gas Only, 4 in. Gas Valve
NXCBO4WFT	Cleaver Brooks Watertube, Gas/Oil, 4 in. Gas Valve
NXCBO5FT5	Cleaver Brooks Oil Cam Shaft 5 in.
NXCBO5FT12	Cleaver Brooks Oil Cam Shaft 12 in.
NXCGLX34	General Purpose Expandable/Flexible Coupling 12mm X 3/4 in.
NXCGL238/1258	General Purpose Coupling 12mm X 3/8 in./12mm X 5/8 in.
NXCGL1212	General Purpose Coupling 12mm X 1/2 in.
NXCGL1210	Special Purpose Coupling 12mm X 10mm. - Eclipse B.V.
NXCGL1234	General Purpose Coupling 12mm X 3/4 in.
NXCGL12100	General Purpose Coupling 12mm X 1 in.
NXICA345	Industrial Crank Arm 12mm X 5 in.
NXICA678	Industrial Crank Arm 12mm X 8 in.
NXCGL1212SQ	General Purpose Coupling 12mm X 1/2 in. square socket
NXVB5197K	Honeywell 5197 Series Valve bracket and Coupling
NXFG5800	Shaft Filing Guide for 5/8 in. shaft size
NXFG3800	Shaft Filing Guide for 3/8 in. shaft size
NXFG1200	Shaft Filing Guide for 1/2 in. shaft size
NXFG3400	Shaft Filing Guide for 3/4 in. shaft size
NXFG1000	Shaft Filing Guide for 1 in shaft size
NXFG1010	Shaft Filing Guide for 10mm shaft size

For mounting brackets or couplings not listed here, consult the factory. To receive a quote for custom brackets or couplings, please provide a detailed sketch with dimensions and fax to Fireye, Derry New Hampshire attention applications engineering



FIREYE®
 3 Manchester Road
 Derry, New Hampshire 03038 USA
 www.fireye.com

NEXBK-1000
 NOVEMBER 2004